### AMENDMENTS TO THE CLAIMS

The following listing of claims replaces all prior versions, and listings, of claims in the application.

### **Listing of Claims**

- 1. (Original) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:
  - a support member;
  - a cutting device for cutting the tubular member coupled to the support member;
  - an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;
  - a locking device for locking the position of the tubular member relative to the support member;
  - an actuator for displacing the expansion device relative to the support member; wherein the actuator comprises:
    - a first actuator for pulling the expansion device; and
    - a second actuator for pushing the expansion device.
- 2. -49. (Canceled)
- 50.-94. (Canceled)
- 95. (Original) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:
  - a support member;
  - an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;
  - a sealing assembly for sealing an annulus defined between the support member and the tubular member;

a locking device for locking the position of the tubular member relative to the support member; and

an actuator for displacing the expansion device relative to the support member;

wherein the actuator comprises:

- a first actuator for pulling the expansion device; and
- a second actuator for pushing the expansion device.

## 96.-141. (Canceled)

- 142. (Original) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:
  - a support member;
  - a first expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;
  - a second expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;
  - a locking device for locking the position of the tubular member relative to the support member; and

an actuator for displacing the expansion device relative to the support member; wherein the actuator comprises:

- a first actuator for pulling the expansion device; and
- a second actuator for pushing the expansion device.
- 143.-190. (Canceled)
- 191. (Original) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:
  - a support member;
  - an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;
  - a packer coupled to the support member;

a locking device for locking the position of the tubular member relative to the support member; and

an actuator for displacing the expansion device relative to the support member;

wherein the actuator comprises:

- a first actuator for pulling the expansion device; and
- a second actuator for pushing the expansion device.

### 192.-337. (Canceled)

338. (Currently amended) A method of radially expanding and plastically deforming a tubular member, comprising:

positioning the tubular member within a preexisting structure;

- radially expanding and plastically deforming a lower portion of the tubular member to form a bell section;
- radially expanding and plastically deforming a portion of the tubular member above the bell section;
- wherein positioning the tubular member within a preexisting structure comprises locking the tubular member to an expansion device; and
- wherein the radially expanding and plastically deforming the tubular member comprises pulling an expansion device through the tubular member with a first actuator and pushing the expansion device through the tubular member with a second actuator.

#### 339.-543. (Canceled)

- 544. (Original) The apparatus of claim 1, wherein the locking device comprises:
  - a housing defining a plurality of circumferentially spaced apart openings;
  - a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and

- a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
- 545. (Canceled)
- 546. (Original) The apparatus of claim 544, wherein the locking device further comprises:
  - a fluid powered actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
- 547. (Canceled)
- 548. (Original) The apparatus of claim 544, wherein the locking device further comprises:
  - a pressure sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 549. (Canceled)
- 550. (Original) The apparatus of claim 1, wherein at least one of the first and second actuators comprise:
  - a locking device for locking the position of the tubular member relative to the support member.
- 551.-556. (Canceled)
- 557. (Original) The apparatus of claim 550, wherein the locking device comprises:
  - a housing defining a plurality of circumferentially spaced apart openings;
  - a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and

- a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
- 558. (Canceled)
- 559. (Original) The apparatus of claim 557, wherein the locking device further comprises:
  - a fluid powered actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
- 560. (Canceled)
- 561. (Original) The apparatus of claim 557, wherein the locking device further comprises:
  - a pressure sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 562.-575. (Canceled)
- 576. (Currently amended) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:
  - a support member;
    - an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;
    - an actuator coupled to the support member for displacing the expansion device relative to the support member; and
- a locking device for locking the position of the tubular member relative to the support member comprising one or more locking elements for engaging an interior surface of the expandable tubular member;
- The apparatus of claim 50, wherein the actuator comprises:

a locking device <u>assembly</u> for locking the position of the tubular member relative to the support member;

wherein the locking device assembly comprises:

one or more locking elements for engaging an interior surface of the expandable tubular member; and

one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.

577.-578. (Canceled)

- 579. (Currently amended) The apparatus of claim 576, wherein the locking device <u>assembly</u> further comprises:
  - a fluid powered actuator for displacing athe locking element retainer relative to the locking elements.
- 580. (Canceled)
- 581. (Currently amended) The apparatus of claim 576, wherein the locking device <u>assembly</u> further comprises:
  - a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 582. (Canceled)
- 583. (Currently amended) The apparatus of claim 576, wherein the locking device <u>assembly</u> comprises:
  - a housing defining a plurality of circumferentially spaced apart openings;
  - a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and

a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.

### 584. (Canceled)

- 585. (Currently amended) The apparatus of claim 583, wherein the locking device assembly further comprises:
  - a fluid powered actuator coupled to the housing for displacing athe locking element retainer relative to the locking elements.
- 586. (Canceled)
- 587. (Currently amended) The apparatus of claim 583, wherein the locking device assembly further comprises:
  - a pressure sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 588.-594. (Canceled)
- 595. (Currently amended) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:
  - a support member;
  - an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;
  - an actuator coupled to the support member for displacing the expansion device relative to the support member; and
- a locking device for locking the position of the tubular member relative to the support member comprising one or more locking elements for engaging an interior surface of the expandable tubular member;

The apparatus of claim 50, wherein the locking device comprises:

a housing defining a plurality of circumferentially spaced apart openings;

a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and

a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.

- 596. (Canceled)
- 597. (Original) The apparatus of claim 595, wherein the locking device further comprises:
  - a fluid powered actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
- 598. (Canceled)
- 599. (Original) The apparatus of claim 595, wherein the locking device further comprises:
  - a pressure sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 600.-606. (Canceled)
- 607. (Original) The apparatus of claim 95, wherein the locking device comprises:
  - a housing defining a plurality of circumferentially spaced apart openings;
  - a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
  - a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.

- 608. (Canceled)
- 609. (Original) The apparatus of claim 607, wherein the locking device further comprises:
  - a fluid powered actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
- 610. (Canceled)
- 611. (Original) The apparatus of claim 607, wherein the locking device further comprises:
  - a pressure sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 612. (Canceled)
- 613. (Original) The apparatus of claim 95, wherein at least one of the first and second actuators comprise:
- a locking device for locking the position of the tubular member relative to the support member; wherein the locking device comprises:
  - one or more locking elements for engaging an interior surface of the expandable tubular member; and
  - one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
- 614.-615. (Canceled)
- 616. (Original) The apparatus of claim 613, wherein the locking device further comprises:
  - a fluid powered actuator for displacing the locking element retainer relative to the locking elements.

- 617. (Canceled)
- 618. (Original) The apparatus of claim 613, wherein the locking device further comprises:

  a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 619. (Canceled)
- 620. (Original) The apparatus of claim 613, wherein the locking device comprises:
  - a housing defining a plurality of circumferentially spaced apart openings;
  - a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
  - a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
- 621. (Canceled)
- 622. (Original) The apparatus of claim 620, wherein the locking device further comprises:

  a fluid powered actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
- 623. (Canceled)
- 624. (Original) The apparatus of claim 620, wherein the locking device further comprises:
  - a pressure sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 625.-644. (Canceled)

- 645. (Original) The apparatus of claim 142, wherein the locking device comprises:
  - a housing defining a plurality of circumferentially spaced apart openings;
  - a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
  - a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
- 646. (Canceled)
- 647. (Original) The apparatus of claim 645, wherein the locking device further comprises:

  a fluid powered actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
- 648. (Canceled)
- 649. (Original) The apparatus of claim 645, wherein the locking device further comprises:

  a pressure sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a
- 650. (Canceled)

predetermined value.

- 651. (Original) The apparatus of claim 142, wherein at least one of the first and second actuators comprise:
- a locking device for locking the position of the tubular member relative to the support member; wherein the locking device comprises:
  - one or more locking elements for engaging an interior surface of the expandable tubular member; and

one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.

### 652.-653. (Canceled)

- 654. (Original) The apparatus of claim 652, wherein the locking device further comprises:
  - a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
- 655. (Canceled)
- 656. (Original) The apparatus of claim 652, wherein the locking device further comprises:

  a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 657. (Canceled)
- 658. (Original) The apparatus of claim 651, wherein the locking device comprises:
  - a housing defining a plurality of circumferentially spaced apart openings;
  - a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
  - a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
- 659. (Canceled)
- 660. (Original) The apparatus of claim 658, wherein the locking device further comprises:
  - a fluid powered actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.

- 661. (Canceled)
- 662. (Original) The apparatus of claim 658, wherein the locking device further comprises:

  a pressure sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 663.-676. (Canceled)
- 677. (Original) The apparatus of claim 191, wherein the locking device comprises:

  one or more locking elements for engaging an interior surface of the expandable tubular member; and

  one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
- 678. (Canceled)
- 679. (Original) The apparatus of claim 677, wherein the locking device further comprises:
  a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
- 680. (Canceled)
- 681. (Original) The apparatus of claim 677, wherein the locking device further comprises:

  a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 682. (Canceled)
- 683. (Original) The apparatus of claim 191, wherein the locking device comprises:

  Page 14 of 32

- a housing defining a plurality of circumferentially spaced apart openings;
- a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
- a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
- 684. (Canceled)
- 685. (Original) The apparatus of claim 683, wherein the locking device further comprises:
  - a fluid powered actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
- 686. (Canceled)
- 687. (Original) The apparatus of claim 683, wherein the locking device further comprises:
  - a pressure sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 688. (Canceled)
- 689. (Original) The apparatus of claim 191, wherein at least one of the first and second actuators comprise:
- a locking device for locking the position of the tubular member relative to the support member; wherein the locking device comprises:
  - one or more locking elements for engaging an interior surface of the expandable tubular member; and
  - one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.

- 690.-691. (Canceled)
- 692. (Original) The apparatus of claim 689, wherein the locking device further comprises:
  - a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
- 693. (Canceled)
- 694. (Original) The apparatus of claim 689, wherein the locking device further comprises: a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 695. (Canceled)
- 696. (Original) The apparatus of claim 689, wherein the locking device comprises:
  - a housing defining a plurality of circumferentially spaced apart openings;
  - a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
  - a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
- 697. (Canceled)
- 698. (Original) The apparatus of claim 696, wherein the locking device further comprises:
  - a fluid powered actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
- 699. (Canceled)

- 700. (Original) The apparatus of claim 696, wherein the locking device further comprises:

  a pressure sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
- 701.-751. (Canceled)
- 752. (Original) The method of claim 338, wherein locking the tubular member to an expansion device comprises:

locking the position of the tubular member relative to a support member.

- 753. (Original) The method of claim 752, wherein locking the position of the tubular member relative to a support member comprises:
  - engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations.
- 754. (Original) The method of claim 753, wherein engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations comprises:
  - engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations using one or more engagement members.
- 755. (Original) The method of claim 754, wherein the engagement members are biased out of engagement with the tubular member.
- 756. (Original) The method of claim 752, wherein locking the position of the tubular member relative to a support member comprises:
  - unlocking the position of the tubular member relative to the support member if an operating condition exceeds a predetermined amount.

757. (Original) The method of claim 756, wherein locking the position of the tubular member relative to a support member comprises:

unlocking the position of the tubular member relative to the support member if an operating condition within the tubular member exceeds a predetermined amount.

758. (Original) The method of claim 754, wherein locking the position of the tubular member relative to a support member comprises:

releasing the engagement members from engagement with the tubular member relative to the support member if an operating condition exceeds a predetermined amount.

759.-777. (Canceled)

778. (Original) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:

a support member;

a cutting device for cutting the tubular member coupled to the support member;

an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member; and

a gripping device for gripping the tubular member coupled to the support member.

- 779. (Original) The apparatus of claim 778, wherein the gripping device comprises a plurality of movable gripping elements.
- 780. (Original) The apparatus of claim 779, wherein the gripping elements are moveable in a radial direction relative to the support member.
- 781. (Original) The apparatus of claim 779, wherein the gripping elements are moveable in an axial direction relative to the support member.
- 782. (Original) The apparatus of claim 779, wherein the gripping elements are moveable in a radial and an axial direction relative to the support member.

Appl. No. 10/553,566

Amdt. Dated September 22, 2009

Reply to Office Action of July 6, 2009

783. (Original) The apparatus of claim 779, wherein the gripping elements are moveable from a

first position to a second position; wherein in the first position, the gripping elements do not engage the

tubular member; wherein in the second position, the gripping elements do engage the tubular member;

and wherein, during the movement from the first position to the second position, the gripping elements

move in a radial and an axial direction relative to the support member.

784. (Original) The apparatus of claim 779, wherein the gripping elements are moveable from a

first position to a second position; wherein in the first position, the gripping elements do not engage the

tubular member; wherein in the second position, the gripping elements do engage the tubular member;

and wherein, during the movement from the first position to the second position, the gripping elements

move in a radial direction relative to the support member.

785. (Original) The apparatus of claim 779, wherein the gripping elements are moveable from a

first position to a second position; wherein in the first position, the gripping elements do not engage the

tubular member; wherein in the second position, the gripping elements do engage the tubular member;

and wherein, during the movement from the first position to the second position, the gripping elements

move in an axial direction relative to the support member.

786. (Original) The apparatus of claim 779, wherein, if the tubular member is displaced in a first

axial direction, the gripping device grips the tubular member; and wherein, if the tubular member is

displaced in a second axial direction, the gripping device does not grip the tubular member.

787. (Original) The apparatus of claim 779, wherein the gripping elements are moveable from a

first position to a second position; wherein in the first position, the gripping elements do not engage the

tubular member; wherein in the second position, the gripping elements do engage the tubular member;

and wherein, the gripping elements are biased to remain in the first position.

788. (Original) The apparatus of claim 779, wherein the gripping device further comprises:

an actuator for moving the gripping elements from a first position to a second position;

wherein in the first position, the gripping elements do not engage the tubular member;

Page 19 of 32

wherein in the second position, the gripping elements do engage the tubular member; and wherein the actuator is a fluid powered actuator.

789. (Currently amended) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:

a support member;

a cutting device for cutting the tubular member coupled to the support member;

an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member; and

a sealing device for sealing an interface with the tubular member coupled to the support member;

wherein the sealing device seals an annulus defines between the support member and the tubular member; and

an actuator for displacing the expansion device relative to the support member, wherein the actuator comprises:

a first actuator for pulling the expansion device; and a second actuator for pushing the expansion device.

790. (Currently amended) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:

a support member;

a cutting device for cutting the tubular member coupled to the support member;

an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member; and

a locking device for locking the position of the tubular member relative to the support member; and

an actuator for displacing the expansion device relative to the support member, wherein the actuator comprises:

a first actuator for pulling the expansion device; and a second actuator for pushing the expansion device.

791. (Canceled)

792. (Currently amended) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:

a support member;

a cutting device for cutting the tubular member coupled to the support member;

an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member; and

a packer assembly coupled to the support member The apparatus of claim 791, wherein the packer assembly comprises:

a packer; and

a packer control device for controlling the operation of the packer coupled to the support member.

- 793. (Original) The apparatus of claim 792, wherein the packer comprises: a support member defining a passage;
  - a shoe comprising a float valve coupled to an end of the support member; one or more compressible packer elements movably coupled to the support member; and a sliding sleeve valve movably positioned within the passage of the support member.
- 794. (Original) The apparatus of claim 792, wherein the packer control device comprises: a support member; one or more drag blocks releasably coupled to the support member; and a stinger coupled to the support member for engaging the packer.
- 795. (Original) The apparatus of claim 792, wherein the packer comprises:
  - a support member defining a passage;
  - a shoe comprising a float valve coupled to an end of the support member;

one or more compressible packer elements movably coupled to the support member;

and

a sliding sleeve valve positioned within the passage of the support member; and Page 21 of 32

wherein the packer control device comprises:

a support member;

one or more drag blocks releasably coupled to the support member; and

a stinger coupled to the support member for engaging the sliding sleeve valve.

796. (Canceled)

797. (Currently amended) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:

a support member;

a cutting device for cutting the tubular member coupled to the support member;

an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member; and

an actuator for displacing the expansion device relative to the support member The apparatus of elaim 796, wherein the actuator comprises:

a first actuator for pulling the expansion device; and

a second actuator for pushing the expansion device.

798. (Currently amended) The apparatus of claim <u>797796</u>, wherein <u>at least one of the first actuator and the second actuator</u> comprises means for transferring torsional loads between the support member and the expansion device.

799. (Canceled)

- 800. (Currently amended) The apparatus of claim <u>797796</u>, wherein <u>at least one of the first actuator</u> and the second actuator comprises a plurality of pistons positioned within corresponding piston chambers.
- 801. (Canceled) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:

a support member;

a cutting device for cutting the tubular member coupled to the support member;

an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member; wherein the cutting device comprises:

a support member; and

a plurality of movable cutting elements coupled to the support member; and

an actuator coupled to the support member for moving the cutting elements between a first position and a second position;

wherein in the first position, the cutting elements do not engage the tubular member; and wherein in the second position, the cutting elements engage the tubular member.

802. (Currently amended) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:

a support member;

a cutting device for cutting the tubular member coupled to the support member;

an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;

wherein the cutting device comprises:

a support member; and

a plurality of movable cutting elements coupled to the support member;

an actuator coupled to the support member for moving the cutting elements between a first position and a second position;

wherein in the first position, the cutting elements do not engage the tubular member; and

wherein in the second position, the cutting elements engage the tubular member; and The apparatus of claim 801, further comprising:

- a sensor coupled to the support member for sensing the internal diameter of the tubular member.
- 803. (Original) The apparatus of claim 802, wherein the sensor prevents the cutting elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.

- 804. (Original) The apparatus of claim 801, wherein the cutting elements comprise:
  - a first set of cutting elements; and
  - a second set of cutting elements;
  - wherein the first set of cutting elements are interleaved with the second set of cutting elements.
- 805. (Original) The apparatus of claim 804, wherein in the first position, the first set of cutting elements are not axially aligned with the second set of cutting elements.
- 806. (Original) The apparatus of claim 804, wherein in the second position, the first set of cutting elements are axially aligned with the second set of cutting elements.
- 807. (Canceled)
- 808. (Currently amended) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:
  - a support member;
  - a cutting device for cutting the tubular member coupled to the support member;
- an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;
  - wherein the expansion device comprises:
    - a support member; and
  - a plurality of movable expansion elements coupled to the support member; and The apparatus of claim 807, further comprising:
  - an actuator coupled to the support member for moving the expansion elements between a first position and a second position;
  - wherein in the first position, the expansion elements do not engage the tubular member; and wherein in the second position, the expansion elements engage the tubular member.
- 809. (Original) The apparatus of claim 808, further comprising:

- a sensor coupled to the support member for sensing the internal diameter of the tubular member.
- 810. (Original) The apparatus of claim 809, wherein the sensor prevents the expansion elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.
- 811. (Original) The apparatus of claim 808, wherein the expansion elements comprise:
  - a first set of expansion elements; and
  - a second set of expansion elements;
  - wherein the first set of expansion elements are interleaved with the second set of expansion elements.
- 812. (Original) The apparatus of claim 811, wherein in the first position, the first set of expansion elements are not axially aligned with the second set of expansion elements.
- 813. (Original) The apparatus of claim 811, wherein in the second position, the first set of expansion elements are axially aligned with the second set of expansion elements.

- a cutting device for cutting the tubular member coupled to the support member; and Page 25 of 32

an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;

wherein the expansion device comprises a plurality of expansion devices.

- 816. (Original) The apparatus of claim 815, wherein at least one of the expansion devices comprises an adjustable expansion device.
- 817. (Original) The apparatus of claim 816, wherein the adjustable expansion device comprises: a support member; and a plurality of movable expansion elements coupled to the support member.
- 818. (Original) The apparatus of claim 817, further comprising:

  an actuator coupled to the support member for moving the expansion elements between a first position and a second position;

  wherein in the first position, the expansion elements do not engage the tubular member; and wherein in the second position, the expansion elements engage the tubular member.
- 819. (Original) The apparatus of claim 818, further comprising:
  a sensor coupled to the support member for sensing the internal diameter of the tubular member.
- 820. (Original) The apparatus of claim 819, wherein the sensor prevents the expansion elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.
- 821. (Original) The apparatus of claim 818, wherein the expansion elements comprise:

  a first set of expansion elements; and
  a second set of expansion elements;
  wherein the first set of expansion elements are interleaved with the second set of expansion elements.

- 822. (Original) The apparatus of claim 821, wherein in the first position, the first set of expansion elements are not axially aligned with the second set of expansion elements.
- 823. (Original) The apparatus of claim 821, wherein in the second position, the first set of expansion elements are axially aligned with the second set of expansion elements.
- 824.-831. (Canceled)
- 831. (Original) The apparatus of claim 829, wherein in the second position, the first set of cutting elements are axially aligned with the second set of cutting elements.
- 832. (Original) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:
  - a support member;
  - a cutting device for cutting the tubular member coupled to the support member;
- an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member; and
- a gripping device for gripping the tubular member coupled to the support member, wherein the gripping device comprises a plurality of movable gripping elements;
- wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, the gripping elements are biased to remain in the first position.
- 833. (Currently amended) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:
  - a support member;
  - an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;
  - an actuator coupled to the support member for displacing the expansion device relative to the support member, wherein the actuator comprises:

a first actuator for pulling the expansion device; and a second actuator for pushing the expansion device; and

a sealing device for sealing an interface with the tubular member coupled to the support member;

wherein the sealing device seals an annulus defines between the support member and the tubular member.

# 834. (Canceled)

835. (Currently amended) An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:

a support member;

an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;

an actuator coupled to the support member for displacing the expansion device relative to the support member; and

a packer assembly coupled to the support member The apparatus of claim 834, wherein the packer assembly comprises:

a packer; and

a packer control device for controlling the operation of the packer coupled to the support member.

836. (Original) The apparatus of claim 835, wherein the packer comprises:

a support member defining a passage;

a shoe comprising a float valve coupled to an end of the support member;

one or more compressible packer elements movably coupled to the support member; and

a sliding sleeve valve movably positioned within the passage of the support member.